

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Conloc UV 665 farbig

Product group: Klebstoffe

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

UV curing adhesive

1.3. Details of the supplier of the safety data sheet

Company name: EGO Dichtstoffwerke GmbH & Co.Betriebs KG

Street: Lilienthalstraße 7
Place: GB-82205 Gilching

Telephone: 08105-217-0 Telefax: 08105-217-33

e-mail: Forster-Hummel@ego.de P.Goldmann@ego.de

Contact person: Eva Forster-Hummel; Telephone: - 28; -27

Petra Goldmann

Internet: http://www.ego.de

Responsible Department: Labor

1.4. Emergency telephone
number:(+49)55119240 (24h/7d)GIZ-Nord, Göttingen

Member of EPECs network

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Dam. 1 Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3 Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements: Causes skin irritation.

May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

Isobornylacrylat

2-hydroxyethyl methacrylate acrylic acid, prop-2-enoic acid

tert-Butylperbenzoat

Signal word: Danger



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 2 of 10

Pictograms:







Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing vapour.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local regulation.

2.3. Other hazards

Do not expose skin and above all eyes to direct or reflected UV light during curing.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of substances listed below with nonhazardous additions.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 3 of 10

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regula				
5888-33-5	Isobornylacrylat	< 50 %			
	227-561-6				
	Skin Irrit. 2, Eye Irrit. 2, STOT SE				
868-77-9	2-hydroxyethyl methacrylate	< 25 %			
	212-782-2	607-124-00-X			
	Eye Irrit. 2, Skin Irrit. 2, Skin Sens				
7473-98-5	2-Hydroxy-2-methylpropiophenone	< 5 %			
	231-272-0				
	Acute Tox. 4; H302				
79-10-7	acrylic acid, prop-2-enoic acid	< 5 %			
	201-177-9	607-061-00-8			
	Flam. Liq. 3, Acute Tox. 4, Acute Think H332 H312 H302 H314 H400				
614-45-9	tert-Butylperbenzoat	< 2,5 %			
	210-382-2				
	Self-react. CD, Acute Tox. 4, Skin				

Full text of H and EUH statements: see section 16.

Further Information

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

If you feel unwell, seek medical advice (show the label where possible).

After inhalation

Move to fresh air in case of accidental inhalation of vapours. Consult physician if problems persist. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.

After ingestion

Consult a physician.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

Treat symptomatically.

SECTION 5: Firefighting measures



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 4 of 10

5.1. Extinguishing media

Suitable extinguishing media

Dry powder, Foam, Carbon dioxide (CO2).

Extinguishing materials should be selected according to the surrounding area.

Unsuitable extinguishing media

High volume water jet

5.2. Special hazards arising from the substance or mixture

Fire may cause evolution of: nitrogen oxides (NOx), Carbon oxides

Heating or fire can release toxic gas.

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Do not breath vapour. Wear personal protection equipment.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

If the product contaminates rivers and lakes or drains inform respective authorities.

6.3. Methods and material for containment and cleaning up

Prevent spreading over a wide area (e.g. by containment or oil barriers).

Substantial quantities: Soak up with inert absorbent material.

Small amounts: Wipe up with absorbent material (e.g. cloth, fleece).

Provide adequate ventilation.

6.4. Reference to other sections

See also section 7, 8, 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin and eyes. Provide sufficient air exchange and/or exhaust in work rooms. Keep away from direct sunlight.

Advice on protection against fire and explosion

Keep away from heat.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep tightly closed in a dry and cool place. Protect against light. Never return unused material to storage receptacle.

Advice on storage compatibility

not required under normal use

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Additional advice on limit values

2-Hydroxyethylmethacrylat



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 5 of 10

MAK see chapter IIb

8.2. Exposure controls

Appropriate engineering controls

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Do not expose skin and above all eyes to direct or reflected UV light during curing.

Protective and hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

Avoid contact with skin. Avoid contact with eyes. Do not breath vapour.

Wash hands when done working with material; at breaks, lunch, shift changes, etc. Take off immediately all contaminated clothing

When using, do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs.

Eye/face protection

Safety glasses with side-shields.

Hand protection

Protective gloves: Glove material Nitrile rubber (0,35 mm), butyl-rubber (0,5 mm) Break through time >= 8h. As the product is a mixture of several substances, the durability of the glove materials cannot be calculated in advance and has to be tested before use.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Skin protection

Long sleeved clothing

Respiratory protection

Ensure adequate ventilation, especially in confined areas.

In case of insufficient ventilation wear suitable respiratory equipment.

Environmental exposure controls

Do not allow material to contaminate ground water system.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: various
Odour: characteristic

Test method

Revision date: 14.12.2015

pH-Value: not applicable

Changes in the physical state

Melting point:
Initial boiling point and boiling range:

Flash point:

not determined
not determined

>100 °C

Explosive properties

The product is: not Explosive.

Density: approx. 1,1 g/cm³
Water solubility: insoluble



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 6 of 10

approx. 100 mPa·s

Viscosity / dynamic:

(at 20 °C)

Solvent content: 0 %

9.2. Other information

The product is: not auto-flammable

SECTION 10: Stability and reactivity

10.2. Chemical stability

No decomposition if used as directed.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Exposure to light.

10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

10.6. Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as:

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure routes	Method	Dose	Species	Source	
5888-33-5	Isobornylacrylat					
	oral	LD50	4350 mg/kg	rat		
	dermal	LD50	> 3000 mg/kg	rabbit		
868-77-9	2-hydroxyethyl methacrylate					
	oral	LD50	5050 mg/kg	Rat		
7473-98-5	2-Hydroxy-2-methylpropiophenone					
	oral	LD50	1694 mg/kg	rat		
	dermal	LD50	6929 mg/kg	rat	OECD Test Guideline 402	
79-10-7	acrylic acid, prop-2-enoic acid					
	oral	LD50	> 192 mg/kg	Rat		
	dermal	LD50	> 290 mg/kg	Rabbit		
	inhalative (4 h) vapour	LC50	3,6 mg/l	Rat		
	inhalative aerosol	ATE	1,5 mg/l			
614-45-9	tert-Butylperbenzoat					
	oral	LD50	1012 mg/kg	rat		

Irritation and corrosivity

The product causes irritation of eyes, skin and mucous membranes.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 7 of 10

Sensitising effects

May cause sensitisation by skin contact.

STOT-single exposure

Inhalation of vapours in high concentration may cause irritation of respiratory system.

Severe effects after repeated or prolonged exposure

This information is not available.

Carcinogenic/mutagenic/toxic effects for reproduction

This information is not available.

Aspiration hazard

This information is not available.

Specific effects in experiment on an animal

This information is not available.

Practical experience

Observations relevant to classification

This information is not available.

SECTION 12: Ecological information

12.1. Toxicity

Toxic for Fish. Toxic to aquatic organisms.

Do not empty into drains or the aquatic environment. Leakage of alredy small quantities into the soil hazardous to drinking water

CAS No	Chemical name					
	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
5888-33-5	Isobornylacrylat					
	Acute fish toxicity	LC50	1,8 mg/l	96 h	Danio rerio (zebra fish)	
	Acute algae toxicity	ErC50	2,7 mg/l	96 h	Pseudokirchneriella subcapitata (green algae)	
	Acute crustacea toxicity	EC50	1,1 mg/l		Daphnia magna (Water flea)	
868-77-9	2-hydroxyethyl methacrylate					
	Acute fish toxicity	LC50	227 mg/l	96 h	Pimephales promelas	
7473-98-5	2-Hydroxy-2-methylpropiophenone					
	Acute crustacea toxicity	EC50	119 mg/l	48 h	Toxicity to daphnia	OECD Test Guideline 202
79-10-7	acrylic acid, prop-2-enoic acid					
	Acute fish toxicity	LC50	27 mg/l	96 h	Onchorhynchus mykiss	
	Acute crustacea toxicity	EC50	95 mg/l	48 h	Daphnia magna	

12.3. Bioaccumulative potential

This information is not available.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
868-77-9	2-hydroxyethyl methacrylate	0,47
79-10-7	acrylic acid, prop-2-enoic acid	0,35

12.4. Mobility in soil

This information is not available.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 8 of 10

12.5. Results of PBT and vPvB assessment

not applicable

12.6. Other adverse effects

This information is not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Dispose of as special waste in compliance with local and national regulations.

Waste disposal number of waste from residues/unused products

080409 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

 ${\tt COATINGS~(PAINTS,~VARNISHES~AND~VITREOUS~ENAMELS),~ADHESIVES,~SEALANTS~AND~PRINTING~INKS;~wastes~from~MFSU~of~adhesives~and~sealants~(including~waterproofing~products);}$

waste adhesives and sealants containing organic solvents or other hazardous substances

Classified as hazardous waste.

Contaminated packaging

Dispose of waste according to applicable local, state, and federal regulations.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Acrylic acid. isobornylacrylate)

14.3. Transport hazard class(es):914.4. Packing group:III

Hazard label: 9



Classification code: M6

Special Provisions: 274 335 601

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 90
Tunnel restriction code: E

Other applicable information (land transport)

Special Provisions 375

Marine transport (IMDG)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

(Acrylic acid. isobornylacrylate)

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 9 of 10



Marine pollutant:yesSpecial Provisions:274, 335Limited quantity:5 LExcepted quantity:E1EmS:F-A, S-FSegregation group:acids

Other applicable information (marine transport)

Special provisions: 274, 909, 944

Air transport (ICAO)

14.1. UN number: UN 3082

14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

14.3. Transport hazard class(es):914.4. Packing group:IIIHazard label:9



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A97 A158

30 kg G

Y964

Excepted quantity:

E1

IATA-packing instructions - Passenger: 964
IATA-max. quantity - Passenger: 450 L
IATA-packing instructions - Cargo: 964
IATA-max. quantity - Cargo: 450 L

Other applicable information (air transport)

Special provisions: A97 A158

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: yes



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2004/42/EC (VOC): 0,0%

National regulatory information

Water contaminating class (D): 2 - water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Conloc UV 665 farbig

Print date: 30.03.2016 Product code: 740665613 Page 10 of 10

Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,6,7,8,9,11,12,13,14,15.

Relevant H and EUH statements (number and full text)

H226	Flammable liquid and vapour.
H242	Heating may cause a fire.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.

Further Information

H411

These data describe only the safety requirements for the product(s) and are based on our present knowledge. However, they do not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)